

Model	Pitch	Roller link Width(Min)	Roller Dia(Max)	Pin Link Plate Thickness	Roller Link Plate Thickness	Roller Link Plate Height(Max)	Pin Dia. (Max)	Over~All Width Riv.(Max)	Over ~All Width Con(Max)	Tensile Strength Min
symbol	P	W	D	T1	T2	H	d	F	G	
unit	mm	mm	Mm	mm	mm	mm	mm	mm	Mm	kgf
415H	12.7	4.7	7.77	1.5	1.5	12	3.97	13.10	14.75	1650
420	12.7	6.25	7.77	1.5	1.5	12	3.97	14.80	16.35	1650
420DX	12.7	6.25	7.77	1.5	1.5	12	3.97	15.0	16.75	1800
420H	12.7	6.25	7.77	2.0	2.0	12	3.97	16.9	18.55	1800
428	12.7	7.85	8.5	1.5	1.5	12.35	4.47	16.50	17.85	1800
428H	12.7	7.85	8.5	1.8	1.8	12.2	4.47	17.60	19.05	2000
428HG	12.7	7.85	8.5	2.0	2.0	12.1	4.51	18.90	20.25	2300
520	15.875	6.4	10.16	2.0	2.0	15	5.09	17.20	18.80	2800
530	15.875	9.5	10.16	2.0	2.0	15	5.09	20.30	21.90	2800